

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,  
T. 10 N., R. 39 E., MDM, NEVADA

CHAINS 40.00	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 7 and 8.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R39E <math>\frac{1}{4}</math> S 7   S 8</p> <p style="text-align: center;">1977</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
80.00	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R39E S 6   S 5 S 7   S 8</p> <p style="text-align: center;">1977</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Land, rolling. Soil, sandy clay and rocky. Undergrowth, sagebrush.</p>
40.00	<p>N. <math>0^{\circ} 03'</math> W., bet. secs. 5 and 6.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 6.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R39E <math>\frac{1}{4}</math> S 6   S 5</p> <p style="text-align: center;">1977</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
84.40	<p>Intersect the Second Standard Parallel North.</p> <p>Point for the closing cor. of secs. 5 and 6.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>