

DEPENDENT RESURVEY OF THE EAST BOUNDARY,
T. 35 N., R. 66 E., MDM, NEVADA

CHAINS	
	<p>reset the original wooden post and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p>
	<p>N. 0° 33' W., bet. secs. 1 and 6.</p>
	<p>Over nearly level land, covered with sagebrush and bunch grass.</p>
49.40	<p>Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T35N R66E R67E ¼ S 1 S 6</p>
	<p style="text-align: center;">1978</p>
	<p>set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p>
86.30	<p>Trail road, bears ESE. and WNW.</p>
103.12	<p>The closing cor. of Tps. 35 N., Rs. 66 and 67 E., monumented with a rebar ½ ins. diam., 16 ins. long, firmly set 10 ins. in the ground. This is accepted as the best existing evidence of the position of the original corner.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R66E S 36 S 1 S 6 CC T35N R66E R67E</p>
	<p style="text-align: center;">1977</p>
	<p>reset the rebar and set a steel fence post, 5½ ft. long, 22 ins. in the ground alongside the iron post.</p>
	<p>From this corner, the standard ¼ sec. cor. of sec. 36, T. 36 N., R. 66 E., monumented with an iron post, 2½ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 36 N., R. 66 E., executed concurrently under this same group, bears S. 89° 43' W., 5.94 chs. dist.</p>