

DEPENDENT RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 66 E., MDM, NEVADA

CHAINS		
	<p>N. 2° 15' W., bet. secs. 1 and 2.</p> <p>Over nearly level land, covered with sagebrush and bunch grass.</p> <p>42.73 Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R66E $\frac{1}{4}$ S 21S 1 1978</p> <p>set a steel fence post, $5\frac{1}{2}$ ft. long, 2 ft. in the ground, alongside the iron post.</p>	
	<p>88.77 Point for the closing cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R66E S 35 <u>S 21S 1</u> CC T35N 1977</p> <p>set a steel fence post, $5\frac{1}{2}$ ft. long, 2 ft. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p> <p>From this cor. the standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 36 N., R. 66 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set, showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 36 N., R. 66 E., executed concurrently under this same group, bears S. 89° 59' W., 5.39 chs. dist.</p>	
	<p>Point for the N. $\frac{1}{4}$ sec. cor. of sec. 1, at midpoint bet. the closing corners and on the S. bdy. of sec. 36, T. 36 N., R. 66 E.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S 1 <u>T35N R66E</u> 1977</p>	