

DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH,  
THROUGH R. 66 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF THE SEVENTH STANDARD PARALLEL NORTH,  
THROUGH RANGE 66 EAST, MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
D.H. Barker and J. H. Eaton, U.S. Deputy Surveyors,  
in 1880,  
and a Portion Resurveyed by  
U.S. Surveyor Newton E. Potter,  
in 1914.

From the standard cor. of Tps. 36 N., Rs. 66 and 67 E.,  
monumented with a wooden post,  $1\frac{1}{2}$  ins. square, 12 ins.  
long, wired to a steel fence post, with illegible scribe  
marks visible.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.

SC  
T36N  
R66E R67E  
S 36 | S 31

1977

deposit the original wooden post and reset the steel  
fence post,  $5\frac{1}{2}$  ft. long, 22 ins. in the ground,  
alongside the iron post and raise a mound of stone, 3  
ft. base, 2 ft. high, N. of cor.

S.  $89^{\circ} 43'$  W., along the S. bdy. of sec. 36.

Over nearly level land, through scattered sagebrush and  
shadscale.

34.10 The closing cor. of Tps. 35 N., Rs. 66 and 67 E.,  
monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set  
and exposed 6 ins. above the ground, with brass cap mkd.  
as described in the field notes of the dependent  
resurvey of the E. bdy. of T. 35 N., R. 66 E., executed  
under this same group.

40.04 Point for the standard  $\frac{1}{4}$  sec. cor. of sec. 36, at  
proportionate distance; there is no remaining evidence  
of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins.  
in the ground, with brass cap mkd.

SC  
T36N R66E  
 $\frac{1}{4}$  S 36

1977

raise a mound of stone, 3 ft. base, 2 ft. high, N. of  
cor.