

406

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 36 N., R. 66 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R66E R67E ¼ S 1 S 6</p> <p style="text-align: center;">1977</p> <p>79.46 The cor. of Tps. 36 and 37 N., Rs. 66 and 67 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy. of T. 37 N., R. 66 E., executed under Group No. 543.</p>
	<p>DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 36 N., R. 66 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <p style="text-align: center;">Reestablishment of a Portion of the Survey Executed by D.H. Barker and J.H. Eaton, U.S. Deputy Surveyors, in 1880.</p> <p>From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 0° 03' E., bet. secs. 35 and 36.</p> <p>Over nearly level land, through scattered sagebrush.</p> <p>36.00 Trail road, bears NNW. and SSE.</p> <p>40.16 Point for the ¼ sec. cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T36N R66E ¼ S 35 S 36</p> <p style="text-align: center;">1977</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>80.32 Point for the cor. of secs. 25, 26, 35 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p>