DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY (SEVENTH STANDARD PARALLEL NORTH), T. 36 N., R. 67 E., MDM, NEVADA

T	
CHAINS	DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY (SEVENTH STANDARD PARALLEL NORTH), T. 36 N., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA
	Reestablishment of the Survey Executed by D. H. Barker and J. H. Eaton, U. S. Deputy Surveyors, in 1880.
	From the standard cor. of secs. 35, and 36, monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 36 N., R. 67 E., executed under Group No. 26.
	S. 89° 45' W., along the S. bdy. of sec. 35.
	Over gently rolling land, covered with sagebrush, greasewood and native grass.
16.20	Power line, bears N. 48 3/4° W. and S. 48 3/4° E.
40.45	Point for the standard $\frac{1}{4}$ sec. cor. of sec. 35, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	SC T36N R67E ½ S 35
	1977
	set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
58.00	
	Power line, bears S. $48\frac{1}{4}^{\circ}$ E. and N. $48\frac{1}{4}^{\circ}$ W.
77.30	Power line, bears S. $48\frac{1}{4}^{\circ}$ E. and N. $48\frac{1}{4}^{\circ}$ W. Underground telephone line, bears S. $48\frac{1}{4}^{\circ}$ E. and N. $48\frac{1}{4}^{\circ}$ W.
	Underground telephone line, bears S. $48\frac{1}{4}^{\circ}$ E. and N. $48\frac{1}{4}^{\circ}$
77.30	Underground telephone line, bears S. $48\frac{1}{4}^{\circ}$ E. and N. $48\frac{1}{4}^{\circ}$ W. Point for the standard cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence
77.30	Underground telephone line, bears S. $48\frac{1}{4}^{\circ}$ E. and N. $48\frac{1}{4}^{\circ}$ W. Point for the standard cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3
77.30	Underground telephone line, bears S. $48\frac{1}{4}^{\circ}$ E. and N. $48\frac{1}{4}^{\circ}$ W. Point for the standard cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock and in a mound of stone, 3 ft. base to top, with brass cap mkd. SC T36N R67E