

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES OF
T. 36 N., R. 67 E., MDM, NEVADA

CHAINS	DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF T. 36 N., R. 67 E., MOUNT DIABLO MERIDIAN, NEVADA
	<p>Reestablishment of the Survey Executed by D. H. Barker and J. H. Eaton U.S. Deputy Surveyors, in 1880</p>
	<p>From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp.</p>
	<p>N. 0° 11' E., bet. secs. 34 and 35.</p>
	<p>Over gently rolling land, covered with sagebrush and scattered juniper.</p>
4.50	Underground telephone line, bears S. 48 3/4° E. and N. 48 3/4° W.
19.10	Powerline, bears S. 48 3/4° E. and N. 48 3/4° W.
40.13	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R67E 1/4 S 34 S 35 1978</p>
	<p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>
57.70	Powerline, bears N. 48 3/4° W. and S. 48 3/4° E.
80.26	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a rebar 1/2 in. diam., 18 ins. long, firmly set 8 ins. above ground. This position is harmoniously related to other existing original corners and is accepted as the best available evidence of the position of the original corner.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R67E S 27 S 26 S 34 S 35 1978</p>