

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF
T. 38 N., R. 57 E., MDM, NEVADA

CHAINS

From the cor. of Tps. 37 and 38 N., Rs. 57 and 58 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above the ground, mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 57 E., executed under Group No. 521.

N. $0^{\circ} 25'$ E., bet. secs. 31 and 36.

Over gently rolling land, through sagebrush.

39.24 The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, monumented with basalt stone, 15 x 15 x 6 ins., mkd. $\frac{1}{4}$ on the W. face, firmly set and exposed 8 ins. above the ground, with a mound of stone W. of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T38N
R57E R58E
 $\frac{1}{4}$
S 36 | S 31

1978

bury the original cornerstone and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. $1^{\circ} 25'$ E., beginning new measurement.

Over nearly level land, through sagebrush and native grasses.

17.00 Trail road, bears NE. and SW.

39.73 Point for the cor. of secs. 25, 30, 31 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T38N
R57E | R58E
S 25 | S 30
S 36 | S 31

1978

set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.