

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY OF  
T. 39 N., R. 57 E., MDM, NEVADA

CHAINS	
	<p>bury the original cornerstone and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p style="text-align: center;">_____</p> <p>S. 89° 55' W., beginning new measurement.</p>
	<p>Over rolling land, through sagebrush; ascend 40 ft. over a S. slope changing to E.</p>
36.55	<p>The closing corner of secs. 5 and 6, T. 38 N., R. 57 E., monumented with an iron post, 2½ ins. diam., hereinafter described.</p>
40.62	<p>The cor. of secs. 31 and 32, monumented with a trachyte stone, 12 x 12 x 6 ins., mkd. with 5 notches on the E. edge and 1 notch on the W. edge, firmly set and exposed 6 ins. above the ground, with a mound of stone W. of cor. and a steel fence post firmly set alongside.</p>
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T39N R57E S 31 S 32 S6 T38N R57E</p>
	<p style="text-align: center;">1977</p>
	<p>bury the original cornerstone and reset the steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>
	<p>S. 89° 27' W., along the S. bdy. of sec. 31.</p>
	<p>Over gently rolling land, through sagebrush; asc. 140 ft. over an E. slope.</p>
29.00	<p>Spur, slopes NE.; desc. 20 ft. over a W. slope.</p>
35.49	<p>The N. ¼ sec. cor. of sec. 6, T. 38 N., R. 57 E., monumented with an iron post, 2½ ins. diam., hereinafter described.</p>
	<p>Desc. 20 ft. over a W. slope.</p>
37.95	<p>The ¼ of sec. 31, monumented with a quartz stone, 15 x 6 x 5 ins., mkd. ¼ on the N. face, firmly set and exposed 8 ins. above the ground, with a mound of stone S. of cor.</p>
	<p>At the corner point</p>