

DEPENDENT RESURVEY OF THE WEST BOUNDARY OF
T. 38 N., R. 57 E., MDM., NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T38N R56E R57E <u>S 1 S 6</u> S 12 S 7</p>
	<p style="text-align: center;">1977</p>
	<p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>
	<p>N. 0° 19' E., bet. secs. 1 and 6.</p>
	<p>Over gently rolling land, through sagebrush; asc. 160 ft. over a SE. slope, changing to E.</p>
33.20	<p>Underground telephone cable, bears S. 75 3/4° W. and N. 75 3/4° E.; asc. 20 ft. over an E. slope.</p>
39.68	<p>Point for the ¼ sec. cor. of sec. 1 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T38N R56E R57E ¼ S 1 S 6</p>
	<p style="text-align: center;">1977</p>
	<p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>
	<p>Ascend 20 ft. over an E. slope.</p>
42.00	<p>Spur, slopes NE.; desc. 260 ft. over a NE. slope.</p>
78.58	<p>The closing corner of Tps. 37 N., Rs. 56 and 57 E., monumented with a basalt stone, 24 x 10 x 8 ins., mkd. with 6 notches on the E., W. and S. edges and CC on top, firmly set in a mound of stone.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T39N R57E <u>S 31</u> S 1 S 6 R56E R57E T38N CC</p>
	<p style="text-align: center;">1977</p>