

DEPENDENT RESURVEY OF A PORTION OF THE  
SUBDIVISIONAL LINES OF  
T. 38 N., R. 57 E., MDM, NEVADA

CHAINS		
	set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.	
40.00	North Fork Humboldt River, 50 lks. wide, 1 ft. deep, course SE.; asc. 240 ft. over a NE. slope.	
76.86	The cor. of secs. 1, 2, 11 and 12.	
	N. 0° 24' E., bet. secs. 1 and 2.	
	Over gently rolling land, through sagebrush; desc. 200 ft. over a NE. slope.	
40.04	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate distance; there is no remaining evidence of the original corner.	
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock and in a mound of stone, $3\frac{1}{2}$ ft. base to top, with brass cap mkd.	
	<p style="text-align: center;">T38N R57E <math>\frac{1}{4}</math> S 21S 1  1978</p>	
50.00	Wash, drains E.; over rolling land.	
72.68	The closing corner of secs. 1 and 2, monumented with a granite stone, 17 x 12 x 10 ins., mkd. with 5 grooves on the W. face, 1 groove on the E. face and CC on the S. face, firmly set and exposed 8 ins. above the ground, with a steel fence post and juniper post firmly set alongside.	
	At the corner point  Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T39N R57E S 36 <hr/>S 21S 1 CC T38N R57E  1978</p>	
	bury the original cornerstone and reset the juniper post and the steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.	