

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISIONAL LINES OF
T. 38 N., R. 57 E., MDM, NEVADA

<p>CHAINS 27.00</p> <p>40.24</p> <p>59.00</p> <p>70.00</p> <p>79.82</p>	<p>Spur, slopes SW.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T38N R57E $\frac{1}{4}$ S 31S 2</p> <p style="text-align: center;">1978</p> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains ENE.</p> <p>Spur, slopes SW.</p> <p>The closing corner of secs. 2 and 3, monumented with a granite stone, 12 x 7 x 5 ins., mkd. with 2 grooves on the E. face, no marks visible on the W. face and CC on the S. face, loosely set in a mound of earth and with a cottonwood post wired to a steel fence post firmly set alongside.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T38N R57E S 35 <hr/>S 31S 2 CC T38N R57E</p> <p style="text-align: center;">1978</p> <p>bury the original cornerstone and reset the wooden post and the steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p> <p>From this corner, the cor. of secs. 34 and 35, T. 39 N., R. 57 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., hereinbefore described, bears N. $89^{\circ} 45'$ W., 2.06 chs. dist.</p> <hr/> <p>Point for the N. $\frac{1}{4}$ sec. cor. of secs. 2, at midpoint between the closing corners and on the S. bdy. of sec. 35, T. 39 N., R. 57 E.</p>
---	---