DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISIONAL LINES OF
T. 38 N., R. 57 E., MDM, NEVADA

CHAINS	
42.60	Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T38N R57E ¼ S 3 S 10 1978 set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
85.20	The cor. of secs. 3, 4, 9 and 10.
	N. 0° 28' E., bet. secs. 3 and 4. Over gently rolling land, through sagebrush.
25.00	Wash, 10 lks. wide, 1 ft. deep, drains ENE.
38.92	Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T38N R57E ¼ S 4 | S 3 1978 set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
77.04	The closing corner of secs. 3 and 4, monumented with a granite stone, 16 x 10 x 10 ins., mkd. with 3 notches on the E. and W. edges, dimly mkd. CC on the S. face and loosely set in a mound of earth, with a steel fence post firmly set alongside. At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T39N R57E S 34 S 4 | S 3 CC T38N R57E 1978