

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISIONAL LINES OF
T. 38 N., R. 57 E., MDM, NEVADA

CHAINS	
38.66	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T38N R57E $\frac{1}{4}$ S 5 S 4</p> <p style="text-align: center;">1978</p> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>
63.00	Trail road, bears NNW. and SE.
64.00	Wash, 10 lks. wide, 1 ft. deep, drains SE.
76.96	<p>The closing corner of secs. 4 and 5, monumented with a granite stone, 19 x 14 x 10 ins., mkd. with 4 notches on the E. edge, 2 notches on the W. edge and CC on the S. face, firmly set and exposed 12 ins. above ground, with a mound of stone W. of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T39N R57E S 33 S 5 S 4 CC T38N R57E</p> <p style="text-align: center;">1978</p> <p>bury the original cornerstone and set a steel fence post, 6 ft. long, 16 ins. in the ground, alongside the iron post.</p> <p>From this corner, the cor. of secs. 32 and 33, T. 39 N., R. 57 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., hereinbefore described, bears N. $89^{\circ} 56'$ W., 3.21 chs. dist.</p>
	<p>Point for the N. $\frac{1}{4}$ sec. cor. of sec. 4, on the S. bdy. of sec. 33, T. 39 N., R. 57 E., at midpoint between the closing corners.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T39N R57E $\frac{1}{4}$ S 4 T38N R57E</p> <p style="text-align: center;">1978</p>