

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISIONAL LINES OF
T. 38 N., R. 57 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T38N R57E

$\frac{1}{4}$
S 6 | S 5

1978

set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.

78.86 The closing corner of secs. 5 and 6, monumented with a limestone, 22 x 10 x 10 ins., mkd. with 5 grooves on the E. face, 1 groove on the W. face and CC on the S. face, firmly set and exposed 8 ins. above ground, with a mound of stone W. of cor.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T39N R57E

S 32

S 6 | S 5

T38N R57E

CC

1977

bury the original cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the cor. of secs. 31 and 32, T. 39 N., R. 57 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., hereinbefore described, bears S. $89^{\circ} 55'$ W., 4.07 chs. dist.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 6, on the S. bdy. of sec. 31 at proportionate distance.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T39N R57E

$\frac{1}{4}$ S 6

T38N R57E

1978

set a steel fence post, $5\frac{1}{2}$ ft. long, 22 ins. in the ground, alongside the iron post.

From this corner, the $\frac{1}{4}$ sec. cor. of sec. 31, T. 39 N., R. 57 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., hereinbefore described, bears S. $89^{\circ} 27'$ W., 2.46 chs. dist.