

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,  
T. 39 N., R. 58 E., MDM, NEVADA

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} T39N R58E \\ S 31   S 32 \\ \hline S 6   S 5 \\ T38N \end{array}$ <p>1978</p> <p>bury the original cornerstone and reset the steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p> <p>N. 89° 42' W., bet. secs. 6 and 31.</p> <p>Over gently rolling land through sagebrush.</p> <p>1.00 Draw, drains WSW.</p> <p>37.00 Spur, slopes S.</p> <p>40.04 Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} T39N R58E \\ \frac{1}{4} \frac{S 31}{S 6} \\ T38N \end{array}$ <p>1978</p> <p>set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p> <p>54.00 Spur, slopes S.</p> <p>71.76 The closing corner of Tps. 38 N., Rs. 57 and 58 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 38 N., R. 57 E., concurrently resurveyed under this same group.</p> <p>Descend 180 ft. over a NW. slope.</p> <p>80.90 The cor. of Tps. 39 N., Rs. 57 and 58 E., monumented with a basalt stone, 18 x 10 x 8 ins., mkd. with 6 notches on the N., E. and W. edges, firmly set in a mound of stone, with a steel fence post firmly set alongside.</p> <p>At the corner point</p>