

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 12 N., R. 44 E., MDM., NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 12 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA.

Reestablishment of the Survey Executed by A. J. Hatch, D. H. Barker and E. L. Bridges, U. S. Deputy Surveyors, in 1873, Resurveyed by Clinton Gurnee, U. S. Deputy Surveyor in 1905, and Resurveyed by Emil Voigt, Cadastral Engineer and Robert C. Yundt, Surveyor in 1933 and 1936.

From the cor. of secs. 34 and 35, on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set and exposed 4 ins. above the ground with brass cap mkd. as described in the remonumentation field notes of T. 12 N., R. 44 E., executed under Group No. 393.
Remark the brass cap as follows:

T12N R44E
S 34 | S 35

S 3
T11N

1961
1978

rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. 89° 54' W., along the S. bdy. of sec. 34.

Over rolling land, through scattered greasewood; asc. 20 ft. over E. slope.

8.30 Rocky knoll; desc. 250 ft. over W. slope.

32.80 The ¼ sec. cor. of sec. 3, T. 11 N., R. 44 E., monumented with an iron post, 1 in. diam., firmly set and exposed 8 ins. above the ground, with brass cap mkd. as described in the field notes of T. 11 N., R. 44 E., executed under Group No. 165. Remark the brass cap as follows:

¼ S 3
T11N R44E

1936
1978

39.90 The original ¼ sec. cor. of sec. 34, monumented with a granite stone, 14 x 6 x 6 ins., firmly set and exposed 4 ins. above the ground, plainly mkd. ¼ on N. face.

At the corner point