

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY,
T. 12 N., R. 44 E., MDM., NEVADA

CHAINS
39.96

The original $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a granite stone, 14 x 6 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T12N R44E} \\ \text{S } 31 \\ \frac{1}{4} \text{ ---} \\ \text{S } 6 \\ \text{T11N} \end{array}$$

1978

bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

S. 72° 25' W., beginning new measurement.

Over gently rolling land, through scattered greasewood; desc. 40 ft. over gradual W. slope.

26.21

The cor. of Tps. 11 and 12 N., Rs. 43 and 44 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the W. bdy. of T. 12 N., R. 44 E., executed under Group No. 545.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
T. 12 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA.

Reestablishment of a Portion of the Survey Executed by
Clinton Gurnee, U. S. Deputy Surveyor,
in 1905.

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the remonumentation field notes of T. 12 N., R. 44 E., executed under Group No. 393. This corner now refers to the cor. of secs. 1 and 12 only. Remark the brass cap as follows:

$$\begin{array}{r} \text{T12N} \\ \text{R44E} \\ \text{S } 11 \\ \text{S } 12 \end{array}$$

1961

1978

rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of cor.