## DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 12 N., R. 44 E., MDM., NEVADA

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 12 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA.  Reestablishment of the Survey Executed by A. J. Hatch, D. H. Barker and E. L. Bridges, U. S. Deputy Surveyors, in 1873, and a portion of the Survey Executed by Clinton Gurnee, U. S. Deputy Surveyor, in 1905.  From the cor. of secs. 1 and 12, on the E. bdy. of the Tp. N. 89° 50' W., bet. secs. 1 and 12.  Over rolling land, through scattered greasewood; desc. 50 ft. over rolling W. slope to \(\frac{1}{2}\) sec. cor.  Trail road, bears NW. and SE.  The original \(\frac{1}{2}\) sec. cor. of secs. 1 and 12, monumented with a limestone, 12 x 10 x 8 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. \(\frac{1}{2}\) on N.  At the corner point  Set an iron post, 28 ins. long, 2\(\frac{1}{2}\) ins. diam., 24 ins. in the ground, with brass cap mkd.  T12N R44E \(\frac{1}{2}\) S 12  1978  bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  N. 89° 52' W., beginning new measurement.  Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.  At the corner point		
Reestablishment of the Survey Executed by A. J. Hatch, D. H. Barker and E. L. Bridges, U. S. Deputy Surveyors, in 1873, and a portion of the Survey Executed by Clinton Gurnee, U. S. Deputy Surveyor, in 1905.  From the cor. of secs. 1 and 12, on the E. bdy. of the Tp.  N. 89° 50' W., bet. secs. 1 and 12.  Over rolling land, through scattered greasewood; desc. 50 ft. over rolling W. slope to ½ sec. cor.  Trail road, bears NW. and SE.  The original ½ sec. cor. of secs. 1 and 12, monumented with a limestone, 12 x 10 x 8 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. ½ on N. face.  At the corner point  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  T12N R44E ½ S 1/S 12  1978  bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  N. 89° 52' W., beginning new measurement.  Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.	CHAINS	
A. J. Hatch, D. H. Barker and E. L. Bridges, U. S. Deputy Surveyors, in 1873, and a portion of the Survey Executed by Clinton Gurnee, U. S. Deputy Surveyor, in 1905.  From the cor. of secs. 1 and 12, on the E. bdy. of the Tp.  N. 89° 50' W., bet. secs. 1 and 12.  Over rolling land, through scattered greasewood; desc. 50 ft. over rolling W. slope to \( \frac{1}{4} \) sec. cor.  28.00  Trail road, bears NW. and SE.  39.77  The original \( \frac{1}{4} \) sec. cor. of secs. 1 and 12, monumented with a limestone, 12 x 10 x 8 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. \( \frac{1}{4} \) on N. face.  At the corner point  Set an iron post, 28 ins. long, 2\( \frac{1}{2} \) ins. diam., 24 ins. in the ground, with brass cap mkd.  T12N R44E \( \frac{1}{2} \) S 1 \( \frac{1}{2} \) S 12  1978  bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  N. 89° 52' W., beginning new measurement.  Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.		
N. 89° 50' W., bet. secs. 1 and 12.  Over rolling land, through scattered greasewood; desc. 50 ft. over rolling W. slope to ½ sec. cor.  28.00 Trail road, bears NW. and SE.  39.77 The original ½ sec. cor. of secs. 1 and 12, monumented with a limestone, 12 x 10 x 8 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. ½ on N. face.  At the corner point  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  T12N R44E  ½ S 1/4 S 12  1978  bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  N. 89° 52' W., beginning new measurement.  Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.		A. J. Hatch, D. H. Barker and E. L. Bridges, U. S. Deputy Surveyors, in 1873, and a portion of the Survey Executed by
N. 89° 50' W., bet. secs. 1 and 12.  Over rolling land, through scattered greasewood; desc. 50 ft. over rolling W. slope to ½ sec. cor.  Trail road, bears NW. and SE.  39.77 The original ½ sec. cor. of secs. 1 and 12, monumented with a limestone, 12 x 10 x 8 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. ½ on N. face.  At the corner point  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  T12N R44E  ½ S 1/2  1978  bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  N. 89° 52' W., beginning new measurement.  Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.		
Trail road, bears NW. and SE.  The original \( \frac{1}{4} \) sec. cor. of secs. 1 and 12, monumented with a limestone, 12 x 10 x 8 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. \( \frac{1}{4} \) on N. face.  At the corner point  Set an iron post, 28 ins. long, 2\( \frac{1}{2} \) ins. diam., 24 ins. in the ground, with brass cap mkd.  \[ \text{T12N R44E} \\ \frac{1}{4} \) \frac{1}{8 12}  \]  bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  N. 89° 52' W., beginning new measurement.  Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.		
The original ½ sec. cor. of secs. 1 and 12, monumented with a limestone, 12 x 10 x 8 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. ½ on N. face.  At the corner point  Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  T12N R44E  1 S 1  1978  bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  N. 89° 52' W., beginning new measurement.  Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.		Over rolling land, through scattered greasewood; desc. 50 ft. over rolling W. slope to $\frac{1}{4}$ sec. cor.
with a limestone, 12 x 10 x 8 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. \( \frac{1}{4} \) on N. face.  At the corner point  Set an iron post, 28 ins. long, 2\( \frac{1}{2} \) ins. diam., 24 ins. in the ground, with brass cap mkd.  \[ \text{T12N R44E} \) \( \frac{1}{4} \) \( \frac{1}{8} \) \( \frac{1}{2} \) \( \frac{1}{8} \) \(	28.00	Trail road, bears NW. and SE.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  T12N R44E  1 S 1  1978  bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  N. 89° 52' W., beginning new measurement.  Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.	39.77	with a limestone, 12 x 10 x 8 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. $\frac{1}{4}$ on N.
in the ground, with brass cap mkd.  T12N R44E  1 S 1  1978  bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  N. 89° 52' W., beginning new measurement.  Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.		At the corner point
1978  bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  N. 89° 52' W., beginning new measurement.  Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.		Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.  N. 89° 52' W., beginning new measurement.  Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.		
N. 89° 52' W., beginning new measurement.  Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.		1978
Over rolling land; desc. 110 ft. over gradual W. slope.  The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.		bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
The original cor. of secs. 1, 2, 11 and 12, monumented with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.		N. 89° 52' W., beginning new measurement.
with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5 notches on S. edge and 1 notch on E. edge.		Over rolling land; desc. 110 ft. over gradual W. slope.
At the corner point	39.97	with a limestone, 12 x 4 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. with 5
		At the corner point
		•