

DEPENDENT RESURVEY OF A PORTION
OF THE SUBDIVISIONAL LINES,
T. 12 N., R. 44 E., MDM., NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T12N R44E S 2 S 1 S 11 S 12</p> <p style="text-align: center;">1978</p> <p>bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>N. 0° 07' E., bet. sec. 1 and 2.</p> <p>Over gently rolling land, along gradual W. slope.</p>
20.70	Trail road, bears WNW. and ESE.
40.11	<p>The original ¼ sec. cor. of secs. 1 and 2, monumented with a granite stone, 12 x 6 x 4 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. ¼ on W. face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T12N R44E ¼ S 2 S 1</p> <p style="text-align: center;">1978</p> <p>bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
	<p>N. 0° 16' E., beginning new measurement.</p> <p>Over gently rolling land.</p>
37.47	<p>Intersect the S. bdy. of sec. 35, T. 13 N., R. 44 E.</p> <p>Point for the closing cor. of secs. 1 and 2.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T13N R44E S 35 S 2 S 1 T12N CC</p> <p style="text-align: center;">1978</p> <p>raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.</p>