

DEPENDENT RESURVEY OF A PORTION  
OF THE SUBDIVISIONAL LINES,  
T. 12 N., R. 44 E., MDM., NEVADA

CHAINS	
	Over gently rolling land; desc. 100 ft. over gradual W. slope.
39.82	The cor. of secs. 2, 3, 10 and 11.
	N. 0° 07' E., bet. secs. 2 and 3.
	Over gently rolling land, through scattered greasewood; over gradual WNW. slope.
40.04	The original $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with a granite stone, 10 x 6 x 4 ins., firmly set and exposed 4 ins. above the ground, plainly mkd. $\frac{1}{4}$ on W. face.
	At the corner point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T12N R44E  <math>\frac{1}{4}</math>  S 3 S 2 </div>
	1978
	bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 0° 10' E., beginning new measurement.
	Over gently rolling land.
11.00	Trail road, bears NW. and SE.
37.31	Intersect the S. bdy. of sec. 34, T. 13 N., R. 44 E.
	Point for the closing cor. of secs. 2 and 3.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T13N R44E  S 34  S 3 S 2  T12N  CC </div>
	1978
	raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.