DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 12 N., R. 44 E., MDM., NEVADA

CHAINS	
3.83	The closing cor. of secs. 3 and 10, hereinbefore described.
40.24	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner. This cor. now refers to the $\frac{1}{4}$ sec. cor. of sec. 4 only.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12N R44E
	1978
	raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
43.85	Point for the W. $\frac{1}{4}$ sec. cor. of sec. 3, on the E. bdy. of sec. 4, and on the E-W center line of sec. 3.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T12N R44E \frac{1}{4} S 3
	1978
	raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.
	From this cor., the (Gurnee) $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with a lava stone, 15 x 6 x 6 ins., firmly set and exposed 6 ins. above the ground, plainly mkd. $\frac{1}{4}$ on W. face, bears N. 89° 54' W., 11.00 chs. dist. Add the marks AM and bury the cornerstone 6 ins. below the surface of the ground.
	From this same cor., the $\frac{1}{4}$ sec. cor. of secs. 2 and 3, bears S. 89° 54' E.
81.09	The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the S. bdy. of T. 13 N., R. 44 E., executed concurrently under this same group.