

DEPENDENT RESURVEY OF THE NORTH BOUNDARY OF  
T. 13 N., R. 44 E., MDM, NEVADA

## CHAINS

set a steel fence post, 5 ft. long, 2 ft. in the ground, alongside the iron post.

- 85.90 The cor. of Tps. 13 and 14 N., Rs. 43 and 44 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the E. bdy. of T. 13 N., R. 43 E., executed under Group No. 545, Nevada. This corner is a Tellurometer traverse station, occupied under Group No. 389, Nevada, which is at latitude  $39^{\circ} 01' 24.28$  N. and longitude  $117^{\circ} 05' 13.12''$  W.

DEPENDENT RESURVEY OF THE NORTH BOUNDARY OF SECTION 1,  
T. 12 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
Clinton Gurnee, U. S. Deputy Surveyor,  
in 1905

From the NE. cor. of sec. 1, T. 12 N., R. 44 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 12 N., R. 44 E., executed concurrently under this same group.

From this corner, a copper-coated steel stake,  $\frac{1}{2}$  in. diam., exposed 8 ins. above the ground, with brass cap mkd. U-59-1, 1961, bears N.  $0^{\circ} 14'$  W., 2.76 chs. dist.

N.  $89^{\circ} 55'$  W., along the N. bdy. of sec. 1.

Over rolling land, through scattered greasewood; desc. 80 ft. over SW. slope changing to a NW. slope.

- 17.93 Point for the  $\frac{1}{4}$  sec. cor. of sec. 36, T. 13 N., R. 44 E., at 40.00 chs. in departure from the SE. cor. of sec. 36; this cor. is located on top of a spur, sloping NW.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 4 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T13N R44E  
 $\frac{1}{4}$  S 36

1978

Desc. 210 ft. over W. slope.

- 39.50 The original  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, monumented with a limestone, 12 x 6 x 3 ins., firmly set and exposed 6 ins. above the ground, plainly mkd.  $\frac{1}{4}$  on N. face. This cor. will now refer to the  $\frac{1}{4}$  sec. cor. of sec. 1 only.