

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 13 N., R. 44 E., MDM, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF THE
SUBDIVISIONAL LINES,
T. 13 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
A. J. Hatch, D. H. Barker and E. L. Bridges,
U. S. Deputy Surveyors, in 1873.

From the SE. cor. of sec. 35, on the S. bdy. of the Tp.
N. 0° 22' E., along the E. bdy. of sec. 35.

Over rolling land, through scattered greasewood, along
gradual W. slope.

- 4.35 The closing cor. of secs. 1 and 36, hereinbefore
described.
- 34.80 Wash, 40 lks. wide, 6 ft. deep, drains W.
- 36.54 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at
proportionate distance; there is no remaining evidence
of the original corner. This corner now refers to the
 $\frac{1}{4}$ sec. cor. of sec. 35 only.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.
- T13N R44E
 $\frac{1}{4}$ |
S 25 |
- 1978
- raise a mound of stone, 3 ft. base, 2 ft. high, W. of
cor.
- 44.32 The $\frac{1}{4}$ sec. cor. of sec. 36, hereinafter described.
- 73.08 The original cor. of secs. 25, 26, 35 and 36, monumented
with a sandstone, 8 x 8 x 8 ins., firmly set and exposed
4 ins. above the ground, plainly mkd. with 1 groove on
the S. face and 1 notch on the E. edge. This corner now
refers to the cor. of secs. 26 and 35 only.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.
- T13N R44E
S 26 | S 36
S 35 |
- 1978
- bury the cornerstone alongside the iron post and raise a
mound of stone, 3 ft. base, 2 ft. high, W. of cor.