

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY OF
T. 34 N., R. 66 E., MDM, NEVADA

CHAINS	
	set a steel fence post, 5½ ft. long, 24 ins. in the ground, alongside the iron post..
	N. 89° 17' W., bet. secs. 5 and 32.
	Over nearly level land, covered with sagebrush, greasewood and shadscale.
38.90	Trail road, on curve, bears NE. and SSW.
40.16	Point for the ¼ sec. cor. of secs. 5 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T34N R66E $\frac{1}{4}$ $\frac{S \ 32}{S \ 5}$ T33N 1978</p>
	set a steel fence post, 5½ ft. long, 24 ins. in the ground, alongside the iron post.
65.50	Telephone line, parallels railroad tracks.
66.20	Western Pacific Railroad Tracks, bears N. 21° E. and S. 21° W.
66.50	Western Pacific Railroad, side tracks, parallels main tracks.
80.32	The cor. of secs. 5, 6, 31 and 32, monumented with a mound of stone. No marked stone found. This is accepted as the best available evidence of the position of the original cor.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T34N R66E $\frac{S \ 31 S \ 32}{S \ 6 S \ 5}$ T33N 1978</p>
	set a steel fence post, 5½ ft. long, 24 ins. in the ground, alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
	N. 89° 07' W., bet. secs. 6 and 31.