

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 67 E., MDM, NEVADA

CHAINS
106.93

Intersect the Seventh Standard Parallel North.

Point for the closing cor. of secs. 2 and 3, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T36N R67E
S 34
S 3 | S 2
CC
T35N R67E

1978

set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.

From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 34, T. 36 N., R. 67 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 36 N., R. 67 E., executed under Group No. 553, bears S. $89^{\circ} 45' W.$, 5.71 chs. dist.

From this same corner, the standard cor. of secs. 34 and 35, T. 36 N., R. 67 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 36 N., R. 67 E., executed under Group No. 553, bears N. $89^{\circ} 45' E.$, 34.74 chs. dist.

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 2, is at midpoint and on the S. bdy. of sec. 35, T. 36 N., R. 67 E.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 2
T35N R67E

1978

set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.

From this corner, the standard cor. of secs. 34 and 35, T. 36 N., R. 67 E., hereinbefore described, bears S. $89^{\circ} 45' W.$, 5.485 chs. dist.