

DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES,
T. 35 N., R. 67 E., MDM, NEVADA

CHAINS	
	<p>N. 0° 43' E., bet. secs. 4 and 5.</p> <p>Over gently rolling land, covered with sagebrush and native grass.</p>
39.20	Trail road and aqueduct, bears ESE. and WNW.
50.81	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T35N R67E $\frac{1}{4}$ S 5 S 4</p> <p style="text-align: center;">1978</p>
	<p>set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.</p>
106.42	<p>Intersect the Seventh Standard Parallel North.</p> <p>Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T36N R67E <u>S 32</u> S 5 S 4 CC T35N R67E</p> <p style="text-align: center;">1978</p>
	<p>set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.</p>
	<p>From this corner, the standard $\frac{1}{4}$ sec. cor. of sec. 32, T. 36 N., R. 67 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 36 N., R. 67 E., executed under Group No. 553, bears S. 89° 45' W., 6.32 chs. dist.</p>
	<p>From this same corner, the standard cor. of secs. 32 and 33, T. 36 N., R. 67 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 36 N., R. 67 E., executed under Group No. 553, bears N. 89° 45' E., 34.21 chs. dist.</p>