

## T. 16 N., R. 63 E., Mount Diablo Meridian, Nevada

## CHAINS

The following field notes are those of the subdivision of section 22 and the survey of Parcel A in section 21, Township 16 North, Range 63 East, Mount Diablo Meridian, Nevada.

The exterior lines of section 22 were surveyed by F. B. Monroe and A. G. Bateman in 1871 and 1872. They were resurveyed by Horace G. Parker and Robert A. Pratt in 1967.

The metes-and-bounds description of Parcel A is recorded in Book 110, pages 208-209, Real Estate Record of White Pine County, Ely, Nevada. It defines the boundary of the Ely Indian Colony.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and special instructions for Group No. 559, Nevada, dated February 21, 1978.

Before restoring or establishing the corners, the pertinent lines of the prior surveys were retraced and diligent search made for all evidence called in prior field note records. The data were thoroughly verified and only the true line field notes are given herein.

The direction of all lines were determined by altitude observations on the sun, and refer to the true meridian.

The geographic position of the  $\frac{1}{4}$  section corner of sections 22 and 27, as scaled from U.S. Geodetic Survey, "COMINS LAKE QUADRANGLE",  $7\frac{1}{2}$  minute series, is as follows:

Latitude:  $39^{\circ} 13.8' N.$  Longitude:  $114^{\circ} 52.2' W.$

The mean magnetic declination is  $16\frac{1}{2}^{\circ} E.$

Subdivision of Section 22,  
T. 16 N., R. 63 E., Mount Diablo Meridian, Nevada

Beginning at the  $\frac{1}{4}$  sec. cor. of secs. 22 and 27, monumented with an iron post,  $2\frac{1}{2}$  ins. diam., loosely set, projecting 12 ins. above the ground, with brass cap mkd. as described in the official record of the 1967 resurvey.

N.  $1^{\circ} 19' W.$ , on the N. and S. center line of sec. 22.

Desc. slightly over rolling NE. slope, through light juniper and sagebrush.

20.15

The center S.  $\frac{1}{16}$  sec. cor. of sec. 22, established by Curtis W. Drollinger, Registered Land Surveyor No. 2793, monumented with a juniper post, 4 ins. diam., firmly set, projecting 3 ft. above the ground and in a mound of stone,  $2\frac{1}{2}$  ft. base, 6 ins. high, with a tag mkd. RLS 2793. This is accepted as a careful and faithful determination of the corner position.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, in a collar of stone, 2 ft. base, to top, with brass cap mkd.