

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
T. 5 S., R. 55 E., MDM, NEVADA

<p>CHAINS 97.50</p>	<p>Rocky spur, slopes NW.; desc. 100 ft. over NE. slope.</p>
<p>100.00</p>	<p>Point for the 100 1/16 sec. cor. of secs. 1 and 2.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., on solid rock over a cross (X) and in a mound of stone to cap, 5 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T5S R55E 1/16 S 2 S 1 100</p> <p style="text-align: center;">1978</p> <p>set a steel fence post, 5 ft. long, alongside the iron post.</p> <p>Descend 270 ft. over NE. slope.</p>
<p>124.31</p>	<p>Intersect the First Standard Parallel South.</p> <p>Point for the closing cor. of secs. 1 and 2.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock and in a collar of stone to cap, 3 ft. base, with brass cap mkd.</p> <p style="text-align: center;">T4S R55E S 32 S 2 S 1 T5S R55E CC</p> <p style="text-align: center;">1978</p> <p>set a steel fence post, 5 ft. long, 18 ins. in the ground, alongside the iron post.</p> <p>From this corner, the standard cor. of secs. 32 and 33, Tp. 4 S., R. 55 E., monumented with an iron post, 2½ ins. diam., exposed 18 ins. above the ground and in a mound of stone to cap, 4 ft. base, with brass cap mkd. as described in the field notes of the dependent resurvey of the First Standard Parallel South, through a portion of R. 55 E., executed under Group No. 548, bears N. 89° 48' E., 8.35 chs. dist.</p> <p>From this same corner, the standard ¼ sec. cor. of sec. 32, Tp. 4 S., R. 55 E., monumented with an iron post, 2½ ins. diam., exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the First Standard Parallel South, through a portion of R. 55 E., executed under Group No. 548, bears S. 89° 48' W., 32.09 chs. dist.</p> <p>Land, rolling to mountainous. Soil, sandy clay and rocky. Timber, juniper; undergrowth, sagebrush.</p>