

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES OF
T. 18½ N., R. 46 E., MDM, NEVADA

CHAINS

Point for the N. ¼ sec. cor. of sec. 2 is on the S. bdy. of sec. 35, T. 19 N., R. 46 E., and at midpoint bet. the closing cors.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

¼ S 2
T18½N R46E

1978

raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the cor. of secs. 35 and 36, T. 19 N., R. 46 E., hereinbefore described, bears EAST 6.00 chs. dist.

From this same corner, the ¼ sec. cor. of sec. 35, T. 19 N., R. 46 E., hereinbefore described, bears WEST 34.00 chs. dist.

GENERAL DESCRIPTION

The area surveyed within Township 18½ North, Range 46 East varies from rolling to gently rolling land. The elevation ranges from about 6300 to 7100 ft. above sea level. The soil varies from sandy clay loam and rocky on the higher elevations to sandy clay loam on the lower land. The vegetation consists of juniper, pinon and sagebrush on the higher elevation to sagebrush, budsage, shadscale and crested wheatgrass on the lower elevation.

U.S. Highway No. 50 crosses through the township in secs. 1, 11 and 12 from SW. to NE. There is a campground located in the north portion of sec. 11.

Principal users of the area are cattlemen and overnight campers. Access into the area is provided by U.S. Highway No. 50 and by numerous improved and unimproved roads. There was no mining activity of consequence noted during the survey.