DEPENDENT RESURVEY OF THE SUBDIVISIONAL LINES, T. 38 N., R. 64 E., MDM, NEVADA

	T. 38 N., R. 64 E., MDM, NEVADA
 CHAINS	From the cor. of secs. 3, 4, 9 and 10.
	S. 89° 33' W., bet. secs. 4 and 9.
	Over rolling land, through medium sagebrush and bunchgrass.
12.50	Wash, 25 1ks. wide, 2 ft. deep, drains SE.
39.56	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T38N R64E
	1 S 4 S 9
-	1978
	set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
57.20	Fence, bears N. $1\frac{1}{4}^{\circ}$ E. and S. $1\frac{1}{4}^{\circ}$ W.
79.12	The cor. of secs. 4, 5, 8 and 9.
	N. 1° 39' W., bet. secs. 4 and 5.
	Over rolling land, through medium sagebrush and bunchgrass.
41.50	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T38N_R64E
	s 5 S 4
	1978
	set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.
65.70	Trail road, bears E. and W.
82.22	The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.
	From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 8 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 37 N., R. 64 E., executed under Group No. 533.