

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY,  
T. 39 N., R. 64 E., MDM, NEVADA

CHAINS		
	<p>N. 89° 18' W., along the S. bdy. of sec. 31.</p>	
	<p>Over rolling land, through medium sagebrush and bunchgrass.</p>	
12.90	<p>Trail road, bears NNW. and SSE.</p>	
21.40	<p>The closing cor. of secs. 31 and 32, T. 38½ N., R. 64 E., hereinafter described.</p>	
40.37	<p>The ¼ sec. cor. of secs. 6 and 31, monumented with a redwood post, 30 ins. long, 1½x3 ins., loosely set in a mound of earth, with illegible scribe marks visible. Hereafter this corner will refer to sec. 31 only.</p>	
	<p>At the corner point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	$\begin{array}{r} T39N \ R64E \\ \frac{1}{4} \quad S \ 31 \\ \hline T38\frac{1}{2}N \ R64E \end{array}$	
	<p>1978</p>	
	<p>deposit the original wooden post and set a steel fence post, 5½ ft. long, 22 ins. in the ground, alongside the iron post.</p>	
	<hr/> <p>N. 88° 46' W., beginning new measurement.</p>	
	<p>Over rolling land.</p>	
19.99	<p>The N. ¼ sec. cor. of sec. 31, T. 38½ N., R. 64 E., hereinafter described.</p>	
40.50	<p>The cor. of Tps. 38 and 39 N., Rs. 63 and 64 E., monumented with a redwood post, 30 ins. long, 2½ ins. square, with illegible scribe marks visible on four sides, wired to a steel fence post. Hereafter this corner will refer to Tp. 38 N., R. 63 E., Tp. 38½ N., R. 64 E., and Tps. 39 N., Rs. 63 and 64 E.</p>	
	<p>At the corner point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	$\begin{array}{r} T39N \\ R63E \ R64E \\ S \ 36 \   \ S \ 31 \\ S \ 1 \ / \ S \ 31 \\ T38N \ / \ T38\frac{1}{2}N \\ R63E \ \ R64E \end{array}$	
	<p>1978</p>	
	<p>deposit the original wooden post and reset the steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.</p>	