TOWNSHIP 39 NORTH, RANGE 65 EAST, MDM, NEVADA

CHAINS

The following field notes are those of the dependent resurvey of the south boundary and a portion of the west boundary of Township 39 North, Range 65 East, Mount Diablo Meridian, Nevada.

The south boundary was surveyed by U.S. Deputy Surveyors D.H. Barker and J.H. Eaton, in 1879 and 1880 under Contract No. 92 and resurveyed by U.S. Deputy Surveyor H. Fitzhugh, in 1894 under Contract No. 186. The west boundary was surveyed by U.S. Deputy Surveyor H.B. Maxson in 1894 under Contract No. 204.

Before restoring the corners, the lines of the original survey were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.

The rules of proportionate measurement were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with the identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 15, 1978, and Supplemental Special Instructions dated September 1, 1978.

The directions of the lines of this survey were determined by azimuth taken from U.S.C. & G.S. triangulation station "IMP" and "NORTH PEQUOP."

The geographic position for the corner of Tps. 38 and 39 N., R.s 65 and 66 E., is at latitude 41° 12' 48.4" N. and longitude 114° 33' 56.1" W., as calculated from U.S.C. & G.S. triangulation station "IMP" located in sec. 27, T. 38 N., R. 64 E.

The magnetic declination was read at a number of stations throughout the township and the mean of these readings was found to be $17\frac{1}{2}^{\circ}$ east.

DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 39 N., R. 65 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by
U.S. Deputy Surveyors D.H. Barker and J.H. Eaton,
in 1879 and 1880,
and Resurveyed by U.S. Deputy Surveyor H. Fitzhugh,
in 1894.

From the cor. of Tps. 38 and 39 N., Rs. 65 and 66 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 38 N., R. 66 E., executed under Group No. 543.