DEPENDENT RESURVEY OF THE SOUTH BOUNDARY, T. 39 N., R. 65 E., MDM, NEVADA

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

1978

reset the original wooden post and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.

From this corner, a U.S.C. & G.S. Bench Mark, monumented with a standard brass tablet, firmly set in concrete, with cap mkd. C 347 1953, bears S. 11° 30' W., 18.79 chs. dist.

S. 89° 51' W., beginning new measurement.

Over gently rolling land.

40.15 The cor. of secs. 4, 5, 32 and 33, monumented with a redwood post, 2x4 ins., 20 ins. long, loosely set in a mound of earth, with illegible scribe marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T39N R65E S 32|S 33 S 5|S 4 T38N

1978

reset the original wooden post and set a steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.

S. 89° 42' W., bet. secs. 5 and 32.

Over gently rolling land, through medium sagebrush and bunchgrass.

7.80 Trail road, bears NE. and SW.

40.81 The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, monumented with a redwood post, 2x4 ins., 30 ins. long, loosely set in a mound of earth, with illegible scribe marks visible.

At the corner point