

## TOWNSHIP 10 NORTH, RANGE 44 EAST, MDM, NEVADA

| CHAINS |   |
|--------|---|
|        | <p>Surveyed M.S. No. 3925 Charles Liddell 1910<br/>           Surveyed M.S. Nos. 4367, 4368, 4369 and 4374 Charles Liddell 1918<br/>           Surveyed M.S. No. 4429 Charles Liddell 1919</p>  |
|        | <p>Other surveys remote to this area not given.</p>   |
|        | <p>Before restoring the corners, the lines of the original surveys were retraced and diligent search made for any evidence of the original corners and other calls of the original field note record.</p>   |
|        | <p>The rules of proportionate measurement and record bearings and distances were applied in order to ascertain the position of lost corners, after completing the necessary retracements to connect with the identified corner locations. In order to simplify the record, the true line notes only are supplied herewith, which refer to the completed survey.</p> |
|        | <p>The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions dated May 30, 1978.</p>   |
|        | <p>The directions of lines were determined by azimuth obtained from the U.S.G.S. triangulation station "SMOKEY", located in T. 10 N., R. 43 E., and carried forward throughout the survey by sustained angulation.</p>  |
|        | <p>The geographic position for the southeast corner of sec. 29, T. 10 N., R. 44 E., is at latitude 38° 41' 22.0" N. and longitude 117° 03' 16.3" W., as calculated along section lines from U.S.G.S. triangulation station "ROUND", located in sec. 19, T. 10 N., R. 44 E.</p>  |
|        | <p>The mean magnetic declination was found to be 16½° east.</p>   |
|        | <hr/> <p>DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,<br/>           T. 10 N., R. 44 E., MOUNT DIABLO MERIDIAN, NEVADA</p> <hr/>   |
|        | <p>Reestablishment of a Portion of the Survey Executed by<br/>           A. J. Hatch, D. H. Barker and E. L. Bridges,<br/>           U. S. Deputy Surveyors, in 1873<br/>           and Resurveyed by Horace G. Parker, Cadastral Surveyor<br/>           in 1961.</p> <hr/>  |
|        | <p>The cor. of secs. 25, 30, 31 and 36, T. 10 N., Rs. 43 and 44 E., monumented with an iron post, 2½ ins. diam., firmly set and exposed 4 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 10 N., R. 43 E., executed under Group No. 384.</p>   |
|        | <p>N. 1° 19' E., bet. secs. 25 and 30.</p>  |
|        | <p>Over rolling land, through scattered greasewood and shadscale; asc. 10 ft. over SW. slope.</p>   |
| 8.00   | <p>Spur, slopes W.; desc. 20 ft. along gradual W. slope to ¼ sec. cor.</p>  |
| 12.00  | <p>Bladed road, bears NNE. and SSW.</p>   |