

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES, T. 10 N., R. 44 E.,
MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 10 N., R. 44 E., MDM, NEVADA

Reestablishment of a Portion of the Survey Executed by
D. H. Barker, U. S. Deputy Surveyor,
in 1874
and a Portion Resurveyed by James R. Munson,
Cadastral Surveyor, in 1975

From the original $\frac{1}{4}$ sec. cor. of secs. 15 and 16,
monumented with a granite stone, 10 x 6 x 4 ins., firmly
set and exposed 6 ins. above the ground, plainly mkd.
on W. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins.
in the ground to bedrock and in a mound of stone to
cap, 3 ft. base, with brass cap mkd.

T10N R44E

$\frac{1}{4}$

S 16|S 15

1978

Bury the cornerstone alongside the iron post.

N. $0^{\circ} 05'$ E., bet. secs. 15 and 16.

Over rolling land, through scattered sagebrush and
greasewood.

7.00 Jefferson Creek, 20 lks. wide, 1 ft. deep, course NW.

40.67 The cor. of secs. 9, 10, 15 and 16, monumented with an
iron post, $2\frac{1}{2}$ ins. diam., firmly set and exposed 4 ins.
above the ground, with brass cap mkd. as described in
the field notes of the dependent resurvey of T. 10 N.,
R. 44 E., executed under Group No. 527.

S. $89^{\circ} 21'$ E., bet. secs. 10 and 15.

Over rolling land, through scattered sagebrush and
greasewood; asc. 160 ft. over gradual W. slope to $\frac{1}{4}$ sec.
cor.

32.40 Trail road, bears NW. and SE.

39.93 The original $\frac{1}{4}$ sec. cor. of secs. 10 and 15, monumented
with a granite stone, 16 x 10 x 8 ins., firmly set and
exposed 10 ins. above the ground and in a circle of
stone, dimly mkd. $\frac{1}{4}$ on N. face.

At the corner point