

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 10 N., R. 44 E., MDM, NEVADA

CHAINS
79.06

Intersect the Second Standard Parallel North.

Point for the closing cor. of secs. 4 and 5, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T11N R44E
S 32
S 5 | S 4
T10N
CC

1978

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

From this corner, the standard cor. of secs. 32 and 33, monumented with an iron post, 2 ins. diam., firmly set and exposed 8 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North, through R. 44 E., executed under Group No. 165, bears S. $89^{\circ} 28'$ E., 5.40 chs. dist.

From this same corner, the standard $\frac{1}{4}$ sec. cor. of sec. 32, monumented with an iron post, 1 in. diam., firmly set and exposed 6 ins. above the ground, with brass cap mkd. as described in the field notes of the dependent resurvey of the Second Standard Parallel North, through R. 44 E., executed under Group No. 165, bears N. $89^{\circ} 28'$ W., 34.60 chs. dist. Remark the brass cap as follows:

SC
T11N R44E
S 32
 $\frac{1}{4}$

1933

1978

Point for the N. $\frac{1}{4}$ sec. cor. of sec. 5 is on the Second Standard Parallel North and at midpoint bet. the closing cors.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 5
T10N R44E

1978

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.