

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 10 N., R. 44 E., MDM, NEVADA

CHAINS	
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R44E <math>\frac{1}{4}</math> <math>\frac{S}{S}</math> <math>\frac{6}{7}</math></p> <p style="text-align: center;">1978</p> <p>Bury the cornerstone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. <math>89^{\circ} 27'</math> W., beginning new measurement.</p> <p>Over rolling land; desc. 60 ft. over NW. slope.</p>
34.12	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.</p>
	<hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. <math>3^{\circ} 09'</math> E., bet. secs. 5 and 6.</p> <p>Over rolling land, through scattered greasewood.</p>
33.20	<p>Indian Creek, 10 lks. wide, 1 ft. deep, course W.</p>
39.78	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p>
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R44E <math>\frac{1}{4}</math> S 6   S 5</p> <p style="text-align: center;">1978</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
79.38	<p>Intersect the Second Standard Parallel North.</p> <p>Point for the closing cor. of secs. 5 and 6, at proportionate distance; there is no remaining evidence of the original corner.</p>