

DEPENDENT RESURVEY OF THE EAST BOUNDARY OF  
T. 14 N., R. 43 E., MDM, NEVADA

## CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T14N  
R43E R44E  
S 12 | S 7  
S 13 | S 18

1978

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N.  $0^{\circ} 36'$  E., bet. secs. 7 and 12.

Over nearly level salt marsh, through medium greasewood, buckbrush and salt grass.

39.77 Point for the  $\frac{1}{4}$  sec. cor. of secs. 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T14N  
R43E R44E  
 $\frac{1}{4}$   
S 12 | S 7

1978

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

51.00 Trail road, bears E. and W.

79.54 Point for the cor. of secs. 1, 6, 7 and 12, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T14N  
R43E R44E  
S 1 | S 6  
S 12 | S 7

1978

raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N.  $0^{\circ} 36'$  E., bet. secs. 1 and 6.

Over nearly level salt marsh, through scattered greasewood, buckbrush and salt grass.