

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY OF  
T. 14 N., R. 43 E., MDM, NEVADA

CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with brass cap mkd.

T15N R43E  
S 32|S 33  
S 5|S 4  
T14N

1978

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY OF  
T. 14 N., R. 43 E., MOUNT DIABLO MERIDIAN, NEVADA

Reestablishment of the Survey Executed by  
C. C. Tracy, U. S. Deputy Surveyor  
in 1867.

The cor. of Tps. 13 and 14 N., Rs. 42 and 43 E., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set and exposed 16 ins. above the ground and in a mound of stone to cap, 4 ft. base, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 13 N., R. 43 E., executed under Group No. 545. This corner is a Tellurometer traverse station occupied under Group No. 389, Nevada, in 1961, and is at latitude  $39^{\circ} 01' 30.864''$  N. and longitude  $117^{\circ} 11' 51.329''$  W., as published on Nevada Protraction Diagram No. 231, Unit No. 58.

N.  $0^{\circ} 20'$  E., bet. secs. 31 and 36.

Over rolling land, through scattered greasewood and shadscale; asc. 50 ft. along rolling E. slope.

40.16 The original  $\frac{1}{4}$  sec. cor. of secs. 31 and 36, monumented with the decayed remains of a wooden post in small pieces, with illegible scribe marks visible, loosely set in center of a circle of stone. This cor. will now refer to the  $\frac{1}{4}$  sec. cor. of sec. 31 only.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T14N  
R43E  
 $\frac{1}{4}$   
|S 31

1978

reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.