DEPENDENT RESURVEY OF THE FOURTH STANDARD PARALLEL NORTH, THROUGH RANGE 43 EAST, MOUNT DIABLO MERIDIAN, NEVADA

CHAINS

DEPENDENT RESURVEY OF
THE FOURTH STANDARD PARALLEL NORTH,
THROUGH RANGE 43 EAST, MDM, NEVADA

Reestablishment of the Survey Executed by William Epler, U. S. Deputy Surveyor in 1865

The Standard cor. of Tps. 21 N., Rs. 43 and 44 E., monumented with an iron post, 3 ins. diam., firmly set and exposed 8 ins. above the ground. This corner was monumented in connection with the retracement and resurvey of the Fourth Standard Parallel North, through R. 44 E., executed under Group No. 30, in 1914, although there is no record of the corner setting or markings in the official field notes. The brass cap is mkd. as follows:

SC T21N R43E|R44E S 36|S 31

1914

rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of cor.

N. 89° 52' W., along the S. bdy. of sec. 36.

Over mountainous land, through scattered sagebrush; asc. 30 ft. over NE. slope.

- 5.54 The closing cor. of Tps. 20 N., Rs. 43 and 44 E., momumented with an iron post, $2\frac{1}{2}$ ins. diam., hereinafter described, on top of spur, sloping NW.; desc. 340 ft. over W. slope.
- 40.12 The original standard $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a quartzite stone, 18 x 7 x 5 ins., firmly set and exposed 12 ins. above the ground in a circle of stone, plainly mkd. $\frac{1}{4}$ on N. face.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

SC T21N R43E ½ S 36

1978

bury the cornerstone alongside the iron post.