

DEPENDENT RESURVEY OF
THE FOURTH STANDARD PARALLEL NORTH,
THROUGH R. 43 E., MDM, NEVADA

CHAINS	
2.10	The N. $\frac{1}{4}$ sec. cor. of sec. 6, monumented with an iron post, $2\frac{1}{2}$ ins. diam., hereinafter described.
34.60	Fence, bears N. and S.
40.43	Point for the standard cor. of Tps. 20 and 21 N., Rs. 42 and 43 E., at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div>SC T21N R42E R43E S 36 S 31 S 1 S 6 T20N 1978</div> set a steel fence post, 5 ft. long, 2 ft. in the ground alongside the iron post. From this corner, the original standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 21 N., R. 42 E., monumented with a granite stone, 16 x 10 x 10 ins., firmly set and exposed 12 ins. above the ground, plainly mkd. $\frac{1}{4}$ on N. face, bears N. $89^{\circ} 54'$ W., 40.43 chs. dist. At the corner point Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to bedrock and in a mound of stone to cap, 3 ft. base, with brass cap mkd. <div>SC T21N R42E $\frac{1}{4}$ S 36</div> 1978 bury the cornerstone and set a steel fence post, 5 ft. long, 16 ins. in the ground, alongside the iron post.
<hr/> DEPENDENT RESURVEY OF THE EAST BOUNDARY, T. 20 N., R. 43 E., MOUNT DIABLO MERIDIAN, NEVADA <hr/>	
Reestablishment of the Survey Executed by C. C. Tracy, U. S. Deputy Surveyor, in 1867, and Resurveyed by Clinton Gurnee, U. S. Deputy Surveyor in 1905 <hr/>	
The cor. of Tps. 19 and 20 N., R. 43 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone to cap, 3 ft. base, with brass cap mkd. as described in the field notes of the dependent resurvey of T. 19 N., R. 43 E., executed under Group No. 414.	