

DEPENDENT RESURVEY OF THE EAST BOUNDARY,  
T. 20 N., R. 43 E., MDM, NEVADA

## CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 4 ins. in the ground to bedrock and in a mound of stone to cap, 5 ft. base, with brass cap mkd.

T20N  
R43E|R44E  
S 12  $\frac{S}{S}$   $\frac{6}{7}$  CC

1978

bury the cornerstone alongside the iron post.

Asc. 100 ft. over S. slope.

39.86 The original cor. of secs. 1 and 12, monumented with a lava stone, 18 x 6 x 6 ins., firmly set and exposed 10 ins. above the ground, plainly mkd., with 5 grooves on the S. face and 1 groove on the N. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 12 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T20N  
R43E|R44E  
S  $\frac{1}{12}$  | S 6

1978

bury the cornerstone alongside the iron post.

N.  $0^{\circ} 33'$  E., along the E. bdy. of sec. 1.

Over mountainous land, through scattered sagebrush; asc. 40 ft. over S. slope.

2.30 Spur, slopes SE.; asc. 220 ft. over rolling E. slope.

40.02 The original  $\frac{1}{4}$  sec. cor. of sec. 1, monumented with a lava stone, 16 x 6 x 6 ins., firmly set and exposed 8 ins. above the ground, plainly mkd.  $\frac{1}{4}$  on W. face.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 6 ins. in the ground to bedrock and in a mound of stone to cap, 4 ft. base, with brass cap mkd.

T20N  
R43E|  
 $\frac{1}{4}$  |  
S 11

1978