

DEPENDENT RESURVEY OF A PORTION OF  
THE SUBDIVISIONAL LINES,  
T. 20 N., R. 43 E., MDM., NEVADA

## CHAINS

- 40.00 The W.  $\frac{1}{4}$  sec. cor. of sec. 5, monumented with an iron post,  $2\frac{1}{2}$  ins. diam., hereinafter described.
- 40.22 The original  $\frac{1}{4}$  sec. cor. of secs. 5 and 6, monumented with a shaved wooden post, 30 ins. long, 2 ins. diam., firmly set and exposed 24 ins. above the ground, scribed  $\frac{1}{4}$  S and other illegible scribe marks visible. This corner will now refer to the  $\frac{1}{4}$  sec. cor. of sec. 6, only.
- At the corner point
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.
- T20N R43E  
 $\frac{1}{4}$  |  
S 6 |
- 1978
- reset the wooden post and set a steel fence post, 5 ft. long, 2 ft. in the ground alongside the iron post.
- 
- N.  $0^{\circ} 29'$  E., beginning new measurement.
- Over rolling land.
- 41.26 Intersect the Fourth Standard Parallel North.
- The original closing cor. of secs. 5 and 6, monumented with the decayed remains of a wooden post, 30 ins. long, 2 ins. square, firmly set and exposed 24 ins. above the ground in a mound of earth, with illegible scribe marks visible.
- At the corner point
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.
- T21N R43E  
S 31  

---

S 6 | S 5  
T20N  
CC
- 1978
- reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
- From this corner, the standard cor. of secs. 31 and 32, hereinbefore described, bears N.  $89^{\circ} 56'$  E., 5.37 chs. dist.
-