

DEPENDENT RESURVEY OF THE NORTH BOUNDARY,
T. 38 N., R. 63 E., MDM, NEVADA

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T39N R63E} \\ \text{S 32} \\ \hline \frac{1}{4} \text{ S 5} \\ \text{T38N} \end{array}$$

1978

deposit the original wooden post and reset the steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.

S. $89^{\circ} 26'$ W., beginning new measurement.

Over gently rolling land.

- 40.54 The cor. of secs. 5, 6, 31 and 32, monumented with an unmarked redwood post, 2x3 ins., 10 ins. long, burned off flush with the ground, lying alongside a steel fence post firmly set and exposed 4 ft. above the ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} \text{T39N R63E} \\ \text{S 31 | S 32} \\ \hline \text{S 6 | S 5} \\ \text{T38N} \end{array}$$

1978

deposit the original wooden post and reset the steel fence post, 6 ft. long, 22 ins. in the ground, alongside the iron post.

N. $89^{\circ} 15'$ W., bet. secs. 6 and 31.

Over gently rolling land, through medium sagebrush and bunchgrass.

- 39.43 The $\frac{1}{4}$ sec. cor. of secs. 6 and 31, monumented with a basalt stone, 17x6x6 ins., mkd. $\frac{1}{4}$ on N. face and firmly set in a mound of stone.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.