## DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 19 N., R. 30 E., MDM, NEVADA

CHAINS

N. 0° 02' 48" W., beginning new measurement.

Over nearly level desert land.

20.291 Point for the N 1/16 sec. cor. of secs. 2 and 3.

Set an aluminum post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with aluminum cap mkd.

> N 1/16 S 3|S 2

> > 1979

set a steel fence post,  $5\frac{1}{2}$  ft. long, alongside the aluminum post.

41.100 The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an aluminum post  $2\frac{1}{2}$  ins. diam., firmly set showing 6 ins. above the ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 20 N., R. 30 E., executed concurrently under this same group.

From the cor. of secs. 22, 23, 26 and 27.

S. 89° 36' 12" W., bet. secs. 22 and 27.

Over nearly level farmland, along Stillwater Road.

10.074 Point for E-E 1/64 sec. cor. of secs. 22 and 27, falls in Stillwater Road.

> Set a 60 D Penny nail, flush with the surface of oil road, from which

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 24 ins. in the ground with a steel fence post,  $5\frac{1}{2}$  ft. long alongside, for a reference monument, bears S. 48° 37' W., 53.9 lks. dist., with brass cap mkd. E-E1/64 S27 RM 1978 35.6 FT and an arrow pointing to the cor.

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 24 ins. in the ground with a steel fence post,  $5\frac{1}{2}$  ft. long alongside, for a reference monument, bears  ${\tt N}.$  $34^{\circ}57'$  W., 72.9 lks. dist., with brass cap mkd. E-E  $1/64\ \text{S22}\ \text{RM}\ 1978\ 48.1\ \text{FT}$  and an arrow pointing to the cor.

20.148 Point for the E 1/16 sec. cor. of secs. 22 and 27, falls in Stillwater Road.

> Set a 60 D Penny nail, flush with the surface of oil road, from which

An iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., set 24 ins. in the ground with a steel fence post,  $5\frac{1}{2}$  ft. long alongside, for a reference monument, bears S.  $43\,^{\circ}$  52' W., 59.4 lks. dist., with brass cap mkd. E 1/16 S27 RM 1978 39.2 FT and an arrow pointing to the cor.