DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES, T. 19 N., R. 30 E., MDM, NEVADA

CHAINS

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T19N R30E $\frac{1}{4}$ S 4|S 3

1978

deposit the original cornerstone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.

N. 0° 06' 18" W., beginning new measurement.

Over nearly level desert land.

21.202 Point for the N 1/16 sec. cor. of secs. 3 and 4.

Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

N 1/16 S 4|S 3

1978

set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.

42.510 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 20 N., R. 30 E., executed concurrently under this same group.

From the cor. of secs. 21, 22, 27 and 28.

S. 89° 46' 24" W., bet. secs. 21 and 28.

Over nearly level farmland, along Stillwater Road.

10.080 Point for the E-E 1/64 sec. cor. of secs. 21 and 28, falls in Stillwater Road.

Set a 60 D Penny nail, flush with the surface of oil road, from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground with a steel fence post, $5\frac{1}{2}$ ft. long alongside, for a reference monument, bears S. 47° 23' W., 62.4 lks. dist., with brass cap mkd. E-E 1/64 S28 RM 1978 41.2 FT and an arrow pointing to the cor.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground with a steel fence post, $5\frac{1}{2}$ ft. long alongside, for a reference monument, bears N. 50° 32' W., 68.2 lks. dist., with brass cap mkd. E-E 1/64 S21 RM 1978 45.0 FT and an arrow pointing to the cor.