

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 19 N., R. 30 E., MDM, NEVADA

CHAINS	
	<p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">S $\frac{1}{16}$ S 5 S 4</p> <p style="text-align: center;">1978</p> <p>set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.</p>
40.040	<p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, monumented with a basalt stone, 14 x 8 x 8 ins., firmly set showing 4 ins. above ground, mkd. $\frac{1}{4}$ on W. face. (Record wooden post).</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">T19N R30E $\frac{1}{4}$ S 5 S 4</p> <p style="text-align: center;">1978</p> <p>deposit the original corner stone and set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.</p> <hr/> <p>N. $0^{\circ} 07' 33''$ E., beginning new measurement.</p> <p>Over nearly level desert land.</p>
20.555	<p>Point for the N $\frac{1}{16}$ sec. cor. of secs. 4 and 5.</p> <p>Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N $\frac{1}{16}$ S 5 S 4</p> <p style="text-align: center;">1978</p> <p>set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the iron post.</p>
40.956	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 20 N., R. 30 E., executed concurrently under this same group.</p> <hr/>