

DEPENDENT RESURVEY OF A PORTION OF
THE SUBDIVISIONAL LINES,
T. 19 N., R. 30 E., MDM, NEVADA

CHAINS	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 89° 19' 39" W., bet. secs. 5 and 8.</p> <p>Over nearly level desert land, covered with sagebrush.</p> <p>20.111 Point for the E 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div><div>E 1/16</div><div><div>S 5</div><div>S 8</div></div></div> <p>1978</p> <p>set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <p>40.222 The ¼ sec. cor. of secs. 5 and 8, monumented with a basalt stone, 10 x 8 x 6 ins., firmly set showing 4 ins. above the ground, mkd. ¼ on N. face. (Record wooden post).</p> <p>At the corner point</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div><div>T19N R30E</div><div><div><div>1</div><div>4</div></div><div><div>S 5</div><div>S 8</div></div></div></div> <p>1978</p> <p>deposit the original corner stone and set a steel fence post, 5½ ft. long, alongside the iron post.</p> <hr/> <p>S. 89° 26' 17" W., beginning new measurement.</p> <p>Over nearly level desert land.</p> <p>20.087 Point for the W 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set an aluminum post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div><div>W 1/16</div><div><div>S 5</div><div>S 8</div></div></div> <p>1978</p> <p>set a steel fence post, 5½ ft. long, alongside the aluminum post.</p> <p>40.174 The cor. of secs. 5, 6, 7 and 8.</p> <hr/> <div><div>SUBDIVISION OF SECTION 2,</div><div>T. 19 N., R. 30 E., MOUNT DIABLO MERIDIAN, NEVADA</div></div> <hr/> <p>From the ¼ sec. cor. of secs. 2 and 11.</p>
--------	--