

SUBDIVISION OF SECTION 2,  
T. 19 N., R. 30 E., MDM, NEVADA

CHAINS	
	N. 0° 22' 51" W., on the N. and S. center line of sec. 2.
	Over nearly level farmland.
40.608	Point for the center $\frac{1}{4}$ sec. cor. of sec. 2, at intersection with the E. and W. center line.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	T19N R30E C $\frac{1}{4}$ S 2
	1979
	set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.
61.936	Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 2.
	Set an aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	C N $\frac{1}{16}$   S 2 C
	1979
	set a steel fence post, $5\frac{1}{2}$ ft. long, alongside the aluminum post.
81.762	The $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set showing 6 ins. above ground, with aluminum cap mkd. as described in the field notes of the dependent resurvey of T. 20 N., R. 30 E., executed concurrently under this same group.
	From the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, determined in the center of Portuguese Lane bearing N. and S. and in line with a fence to the E. This is accepted as the best existing evidence of the original corner.
	At the corner point
	Set a 60 D Penny nail, flush with the surface of the road, from which
	An aluminum post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 24 ins. in the ground with a steel fence post, $5\frac{1}{2}$ ft. long alongside, for a reference monument, bears N. 39° 17' E., 57.3 lks. dist., with aluminum cap mkd. $\frac{1}{4}$ S1 RM 1979 37.8 FT and an arrow pointing to the cor.